HB0153S01 compared with HB0153

{deleted text} shows text that was in HB0153 but was deleted in HB0153S01.

inserted text shows text that was not in HB0153 but was inserted into HB0153S01.

DISCLAIMER: This document is provided to assist you in your comparison of the two bills. Sometimes this automated comparison will NOT be completely accurate. Therefore, you need to read the actual bills. This automatically generated document could contain inaccuracies caused by: limitations of the compare program; bad input data; or other causes.

Representative Norman K Thurston proposes the following substitute bill:

DISPLAY OF LICENSE PLATES

2015 GENERAL SESSION STATE OF UTAH

Chief Sponsor: Mark A. Wheatley

Senate Sponsor:

LONG TITLE

General Description:

This bill modifies the Motor Vehicles code relating to license plates.

Highlighted Provisions:

This bill:

requires that a license plate be {displayed} maintained in a {manner} condition to be {plainly readable} clearly legible from a distance of 100 feet during daylight.

Money Appropriated in this Bill:

None

Other Special Clauses:

None

Utah Code Sections Affected:

AMENDS:

HB0153S01 compared with HB0153

 $\frac{\{41-1a-403\}}{41-1a-404}$, as $\frac{\{1992\}}{2008}$, Chapter $\frac{\{1\}}{106}$

Be it enacted by the Legislature of the state of Utah:

Section 1. Section {41-1a-403}41-1a-404 is amended to read:

41-1a-403. Plates to be legible from 100 feet.

License plates and the required letters and numerals on them, except the decals and the slogan, shall be of sufficient size and displayed in a manner to be plainly readable

341-1a-404. Location and position of plates.

- (1) License plates issued for a vehicle other than a motorcycle, trailer, or semitrailer shall be attached to the vehicle, one in the front and the other in the rear.
- (2) The license plate issued for a motorcycle, trailer, or semitrailer shall be attached to the rear of the motorcycle, trailer, or semitrailer.
 - (3) Every license plate shall at all times be:
 - (a) securely fastened:
- (i) in a horizontal position to the vehicle for which it is issued to prevent the plate from swinging;
- (ii) at a height of not less than 12 inches from the ground, measuring from the bottom of the plate; and
 - (iii) in a place and position to be clearly visible; and
 - (b) maintained:
 - (i) free from foreign materials; and
 - (ii) in a condition to be clearly legible from a distance of 100 feet during daylight.

<u>Legislative Review Note</u>

as of 1-9-15 11:42 AM

Office of Legislative Research and General Counsel.

HB0153S01 compared with HB0153

(4) Enforcement by a state or local law enforcement officer of the requirement under Subsection (1) to attach a license plate to the front of a vehicle shall be only as a secondary action when the vehicle has been detained for a suspected violation by any person in the vehicle of Title 41, Motor Vehicles, other than the requirement under Subsection (1) to attach a license plate to the front of the vehicle, or for another offense.